

PRODUCT INFORMATION

PT PARAHYANGAN KAPUR BUMI INDONESIA

Factory : Jl. Raya Cianjur KM 22.5, Kp. Cinangsi RT. 04 Ds.
Gunung Masigit, Kec. Cipatat, Kab. Bandung Barat
Telp : (022) 6810897 Fax. : (022) 6810912



SAA 400

Specification

- Residue on 200 Mesh ≤ 2.5 %
(ISO 787/7)
- Moisture content ≤ 0.3 %
(ISO 787/2)

Chemical analysis

CaCO ₃	≥ 97 %
MgCO ₃	≤ 1.95 %
Fe ₂ O ₃	≤ 0.20 %
HCL insoluble content	≤ 0.50 %

Physical properties

Density (ISO 787/10)	2.7
Refractive Index	1.59
Hardness (Mohs)	3.0

Application

- Agricultural
- Animal feed
- Board
- Ceramic
- Concrete
- Household
- Mortar
- Soil Treatment
- Water Treatment

Standard packaging

- Small Bag 50 Kg
- Jumbo Bag 1000 Kg
- Hi-blow Truck

TDS-PKBI/R-03/010918

The data provided above are contained available data that using for control our product quality. As the natural product that produced in large quantity, there are any conditions that we have any little tolerant for the data. Hence the data can not be taken as binding.